





PIC



Туре	recessed ceiling luminaire
item nr.	15/2060.07-07/30
GTIN (EAN)	4022671112260

description

Minimal appearance with 100% light. That's the PIC downlight in three different variations. Dimensions of only 50mm, made with intelligent, passive cooling.

Please order LED driver separately

PIC. recessed ceiling luminaire, white - white, LED not

exchangeable, direct, IP20)
material and dimensions	
color	white - white
material	aluminium
dimensions	D 50 mm x H 2 mm
weight	0.1 kg
light and electric specifica	tions
lightsource	LED not exchangeable
control	other
Casambi	optionally available with CASAMBI control
system demand	10 W
net	480 lm (luminaire/net)
gross	1,030 lm (LED- module/gross)

Casambi	CASAMBI control
system demand	10 W
net	480 lm (luminaire/net)
gross	1,030 lm (LED- module/gross)
light color	3,000 K - 3,000 K
CRI	90-100
beam angle	50 °
light emission	direct
degree of protection	IP20
protection class	3
Product type according to EU 2019/2015 and EU 2019/2020	containing product
Energy efficiency class of the built-in light source(s)	F

accessory	
name	LED-Konverter on / off 9 W, 700mA, 13V
item nr.	6050
short text	PIC, accessory
name	LED-Konverter dimmbar 10 W, 700mA, 15 V
item nr.	6051
short text	PIC, accessory
name	CASAMBI CBU-TED
	Bluetooth Dimmer
item nr.	6100
short text	CASAMBI, accessory